MACHINE TUFTED CARPET TILE
PERFORMANCE AND SPECIFICATION

Carpets Inter®

Specification

Collection	: BRIGHT LIGHT BIG CITY : BANGKOK - SIAM SQUARE			
Construction	: Multi-Level Texture Loop			
Yarn Content	: 100% Solution Dyed Nylon			
Machine Gauge	: 1/12	inch		
Pile Height	: 3.0 - 5.0	mm	0.118 - 0.197	inch
Total Weight	: 2605	gm/sm	76.8	oz/sy
Primary Backing	: Non Woven Polyester Spunbonded			
Secondary Backing	: **EcoSoft x®**, Recycled PET Cushion Back			
Tile Size	: 1 x 1	m		

Performance Test and Treatment

Surface Flammability	ASTM D2859 / CPSC FF 1-70 Pill Test Pass
Hot Metal Nut	BS 4790 Low Radius
Radiant Panel Test	ASTM E648 Class 1
Smoke Density	ASTM E662 < 450
Fire Classification	BS EN 13501
Indoor Air Quality	CRI Green Label Plus
Electrostatic Propensity	AATCC 134 < 3.5 KV
End Use Classification	BS EN 1307 Class 33 - Heavy Commercial
Castor Chair Index	BS EN 985 ≥ 2.4
Dimensional Stability	BS EN 986 < 0.20%
Colorfastness to Light	ISO 105 B02 Minimum L6
Sound Absorption	ASTM C423 NRC 0.30 or higher
Treatments	Stain and Soil Protection, Anti Microbial (Optional) & Antiviral (Optional)

LEED Credit Contribution

Material & Resources:

Environmental Product Declarations	Option 1: Environmental Product Declarations (EPD) Option 2. Embodied Carbon/LCA Optimization
Sourcing of Raw Materials	Option 2: Recycled Content
Material Ingredients	Option 1: Material Ingredient Reporting: Health Product Declaration Option 2: Material Ingredient Optimization: REACH Optimization

Indoor Environmental Quality:

Low Emitting Materials	CRI Green Label Plus Certified
Acoustic Performance	Option 2: Acoustical Finishes and Site Exterior Noise

Installation Method



Checkerboard

Certification and Standards

We apply strict quality control at all stages of production, in compliance with ISO 9001. However, the carpet manufacturing process is a complex series of operations and variations in the specifications could occur. This will not have any detrimental effect on the performance of the product. We reserve the right to amend this specification without prior notice.

Disclaimer - Visibility of Modular Carpet Tile butt-joint. Due to the organic nature of some modular carpet tile patterns, there may be occasions where a darker line appears at the side/end seams within some colors, especially for 'Plank' installations. This is a natural characteristic of the random textual effect visible upon the floor and is not considered nor accepted as a product defect.

MACHINE TUFTED CARPET TILE
PERFORMANCE AND SPECIFICATION

Carpets Inter®

Specification

Collection	: BRIGHT LIGHT BIG CITY : BANGKOK - SIAM SQUARE			
Construction	: Multi-Level Texture Loop			
Yarn Content	: 100% Solution Dyed Nylon			
Machine Gauge	: 1/12	inch		
Pile Height	: 3.0 - 5.0	mm	0.118 - 0.197	inch
Total Weight	: 3015	gm/sm	88.9	oz/sy
Primary Backing	: Non Woven Polyester Spunbonded			
Secondary Backing	: **EcoSoft®**, Recycled PET Cushion Back			
Tile Size	: 1 x 1	m		

Performance Test and Treatment

Surface Flammability	ASTM D2859 / CPSC FF 1-70 Pill Test Pass
Hot Metal Nut	BS 4790 Low Radius
Radiant Panel Test	ASTM E648 Class 1
Smoke Density	ASTM E662 < 450
Fire Classification	BS EN 13501
Indoor Air Quality	CRI Green Label Plus
Electrostatic Propensity	AATCC 134 < 3.5 KV
End Use Classification	BS EN 1307 Class 33 - Heavy Commercial
Castor Chair Index	BS EN 985 ≥ 2.4
Dimensional Stability	BS EN 986 < 0.20%
Colorfastness to Light	ISO 105 B02 Minimum L6
Sound Absorption	ASTM C423 NRC 0.35 or higher
Treatments	Stain and Soil Protection, Anti Microbial (Optional) & Antiviral (Optional)

LEED Credit Contribution

Material & Resources:

Environmental Product Declarations	Option 1: Environmental Product Declarations (EPD) Option 2. Embodied Carbon/LCA Optimization
Sourcing of Raw Materials	Option 2: Recycled Content
Material Ingredients	Option 1: Material Ingredient Reporting: Health Product Declaration Option 2: Material Ingredient Optimization: REACH Optimization

Indoor Environmental Quality:

Low Emitting Materials	CRI Green Label Plus Certified
Acoustic Performance	Option 2: Acoustical Finishes and Site Exterior Noise

Installation Method



Checkerboard

Certification and Standards

We apply strict quality control at all stages of production, in compliance with ISO 9001. However, the carpet manufacturing process is a complex series of operations and variations in the specifications could occur. This will not have any detrimental effect on the performance of the product. We reserve the right to amend this specification without prior notice.

Disclaimer - Visibility of Modular Carpet Tile butt-joint. Due to the organic nature of some modular carpet tile patterns, there may be occasions where a darker line appears at the side/end seams within some colors, especially for 'Plank' installations. This is a natural characteristic of the random textual effect visible upon the floor and is not considered nor accepted as a product defect.

Specification

Collection	: BRIGHT LIGHT BIG CITY : BANGKOK - SIAM SQUARE			
Construction	: Multi-Level Texture Loop			
Yarn Content	: 100% Solution Dyed Nylon			
Machine Gauge	: 1/12	inch		
Pile Height	: 3.0 - 5.0	mm	0.118 - 0.197	inch
Total Weight	: 3625	gm/sm	106.9	oz/sy
Primary Backing	: Non Woven Polyester Spunbonded			
Secondary Backing	: **EcoSquare®**, Reinforced Recycled Hard Back			
Tile Size	: 1 x 1	m		

Performance Test and Treatment

Surface Flammability	ASTM D2859 / CPSC FF 1-70 Pill Test Pass
Hot Metal Nut	BS 4790 Low Radius
Radiant Panel Test	ASTM E648 Class 1
Smoke Density	ASTM E662 < 450
Fire Classification	BS EN 13501
Indoor Air Quality	CRI Green Label Plus
Electrostatic Propensity	AATCC 134 < 3.5 KV
End Use Classification	BS EN 1307 Class 33 - Heavy Commercial
Castor Chair Index	BS EN 985 ≥ 2.4
Dimensional Stability	BS EN 986 < 0.20%
Colorfastness to Light	ISO 105 B02 Minimum L6
Sound Absorption	ASTM C423 NRC 0.15 or higher
Treatments	Stain and Soil Protection, Anti Microbial (Optional) & Antiviral (Optional)

LEED Credit Contribution

Material & Resources:

Sourcing of Raw Materials	Option 2: Recycled Content
Material Ingredients	Option 1: Material Ingredient Reporting: Health Product Declaration Option 2: Material Ingredient Optimization: REACH Optimization

Indoor Environmental Quality:

Low Emitting Materials	CRI Green Label Plus Certified
Acoustic Performance	Option 2: Acoustical Finishes and Site Exterior Noise

Installation Method



Checkerboard

Certification and Standards

We apply strict quality control at all stages of production, in compliance with ISO 9001. However, the carpet manufacturing process is a complex series of operations and variations in the specifications could occur. This will not have any detrimental effect on the performance of the product. We reserve the right to amend this specification without prior notice.

Disclaimer - Visibility of Modular Carpet Tile butt-joint. Due to the organic nature of some modular carpet tile patterns, there may be occasions where a darker line appears at the side/end seams within some colors, especially for 'Plank' installations. This is a natural characteristic of the random textual effect visible upon the floor and is not considered nor accepted as a product defect.